

IMM 382
May 1970

Courant Institute of
Mathematical Sciences

Asymptotic Performance of a System Subject to Cannibalization

Warren M. Hirsch and Herman Hanisch

Prepared under Contract N00014-67-A-0467-0004
with the Office of Naval Research NR 042-206

For Presentation to the
NATO CONFERENCE
Luxembourg, May 1970

Distribution of this document is unlimited.



New York University

2-1
C-1
IMM 382

NEW YORK UNIVERSITY
GOVERNMENT INSTITUTE LIBRARY

New York University
Courant Institute of Mathematical Sciences

ASYMPTOTIC PERFORMANCE OF A SYSTEM SUBJECT TO CANNIBALIZATION

Warren M. Hirsch and Herman Hanisch^{*}

This report represents results obtained at the Courant Institute of Mathematical Sciences, New York University, with the support of the Office of Naval Research, Contract N00014-67-A-0467-0004. Reproduction in whole or in part is permitted for any purpose of the United States Government.

Distribution of this document is unlimited.

^{*} City College of New York, C.U.N.Y.

NEW YORK UNIVERSITY
COURANT INSTITUTE-LIBRARY

ABSTRACT

We consider the performance of a system composed of n machines, each machine being composed of parts (or modules) of r different types arranged in series. If S_i denotes the number of parts of type i functioning at a given moment, it is assumed that the performance level, Φ , of the overall system at that moment is given by the equation

$$\Phi = \min_{1 \leq i \leq r} S_i .$$

A collection of identical structures (ships, aircraft, missile batteries, etc.) exemplifies the kind of system we have in mind, under the simplifying assumption that each part in a given structure is essential to the performance of that structure. Limit theorems are proved which make it possible to evaluate explicitly the asymptotic performance level of the system under three different assumptions:

1. Cannibalization is prohibited.
2. A failed part in a given machine can be replaced by an operating part of the same type taken from another machine. The lifetimes of the parts are mutually independent random variables.
3. A failed part in a given machine can be replaced by an operating part of the same type taken from another machine. Failures of parts may affect the lifetimes of other parts.

It is shown that assumptions (2) and (3) lead to asymptotically equivalent performance levels. The superiority of systems in which cannibalization is practiced over those in which it is prohibited is quantitatively appraised.

INTRODUCTION

Among possible ways of maintaining a system¹ whose spares have been exhausted, cannibalization is one that has been practiced over a long period of time by the military of many nations, albeit not always with the consent of the commanding officer. By "cannibalization" we mean the removal of a failed part² from a system and its replacement by an operating part of the same type extracted from another part of the same system. In a system consisting of two aircraft, a simple example of cannibalization is the switching of a damaged tire on one aircraft with a good tire on the second. If, for instance, the radar on the second aircraft is damaged and a replacement is unavailable, the exchange of tires may at least restore one aircraft to operating condition.

The practice of cannibalization is highly controversial primarily because the very act of extracting an operating part from a complex system can cause extensive damage to other parts of the system. On the other hand, in situations where it is crucial to maintain the performance of a system at a high level, a viable alternative to cannibalization may be difficult to find. Because of the importance and polemical nature of cannibalization,

¹The word "system" is not limited to a single physical entity such as an aircraft, ship, missile launcher, etc. It includes also any designated collection of objects whose maintenance and performance as a unit is of interest.

²The failed part can be either a single part or an entire module, i.e., a package of components of a system that can be removed and replaced as a whole. Throughout this paper the word "part" can be interpreted to mean "individual part" or "module".

one of the present authors was led in an earlier paper [1] to develop a mathematical model of a system subject to cannibalization. This model, which is applicable to a very wide class of systems and to parts subject to arbitrary failure distributions, leads to closed form expressions for the probability distribution and expected value of the system performance level. In the present paper we carry further the analysis in [1] by studying in detail a special class of systems whose parts are subject to exponential failure rates. In this special case, as will be shown, it is possible to derive limit theorems that make it computationally feasible to assess the effects of cannibalization and to compare the performance levels and efficiencies of cannibalized and uncannibalized systems.

I. DESCRIPTION OF THE SYSTEM

We consider a collection of n objects, O_1, O_2, \dots, O_n , to be used as a system to carry out a sequence of specified tasks, each task requiring τ units of time to complete. For simplicity we assume that the k -th task is initiated at time $(k-1)\tau$ and completed at time $k\tau$, $k = 1, 2, \dots$.³ We shall refer to each object as a "machine" and to each task as a "mission". We define the size of the system to be the number, n , of objects it contains. A typical example of the kind of system we have in mind is a fleet of destroyers sent on voyages, or a squadron of aircraft sent on reconnaissance missions. We emphasize, however, that the nature of the machines and the kinds of missions performed may be quite arbitrary. Each machine O_j is composed of r distinct parts, $\gamma_{1j}, \gamma_{2j}, \dots, \gamma_{rj}$, $j = 1, 2, \dots, n$, where $r > 1$ and for each index i , $1 \leq i \leq r$, the parts $\gamma_{i1}, \gamma_{i2}, \dots, \gamma_{in}$ are assumed to be replicas of each other.

A machine is sent on a mission if and only if all of its parts are in good working order at the beginning of the mission. If one or more of its parts fails during the course of a mission, it is assumed that the machine returns from the mission, i.e., that the machine and its unfailed parts are available at the end of the mission.⁴ We consider the case when no spare parts are

³Only minor modifications are needed to treat the case when the tasks are carried out during arbitrarily specified non-overlapping intervals of time of length τ .

⁴This assumption is not as pernicious as it may seem, since the machines being considered may be subassemblies of larger pieces of equipment. For example, the machines may be periscopes in submarines; even if the periscope is damaged during the course of a mission, the submarine has the capacity to return to its base.

available and damaged parts are irreparable, so that cannibalization is the only possible mode of maintenance. We assume that for each index i , $1 \leq i \leq r$, the parts $y_{i1}, y_{i2}, \dots, y_{in}$ are freely interchangeable, and that these are the only allowed exchanges. At the conclusion of a given mission k , the system is cannibalized in such a way as to maximize the number of machines that can be dispatched on mission $k+1$. The assumption that missions are dispatched at times $0, \tau, 2\tau, \dots$ and are of duration τ implies that all cannibalizations are instantaneously carried out.⁵

It is convenient to describe the state of each part at a given moment t by means of an ordered pair (x, y) whose first component x indicates the "employment status" of the part at time t and whose second component y indicates the "fitness" of the part at time t . For our analysis it suffices to distinguish two categories of employment: If, at time t , the part is installed in a machine that is then on a mission, we set $x = 1$ and say that the part is "engaged"; if it is in a machine that is not on a mission at time t , we set $x = 0$ and say that the part is "idle."⁶ Concerning fitness, we assume that each part is either in good working order (operational) or has failed (unfit). We set $y = 1$ if the part is in good working order at time t ; otherwise, $y = 0$. Thus, at each instant the state of a given part corresponds to one of the four vertices $(0, 0), (0, 1), (1, 0), (1, 1)$ of the unit

⁵This restriction can easily be removed without essential modification of our conclusions.

⁶We adopt the convention that the instants $0, \tau, 2\tau, \dots$ when the missions are initiated are engaged times for parts in the dispatched machines.

square. It is assumed that all parts are operational at time 0.

We shall analyze the performance of the system under two distinct assumptions concerning the periods when a part is exposed to risk of failure. The first of these, called the assumption of "synchronous clocks," postulates that at every instant t each part which is operational at time t , regardless of its employment status, is subject to risk of failure. This assumption (adopted in [1]) contrasts with the assumption of "asynchronous clocks" (adopted in [2]) according to which a given part is subject to risk of failure at time t if and only if it is in state $(1,1)$ at time t , i.e., engaged and operational.⁷ In both cases — synchronous and asynchronous clocks — it will be assumed that when parts are simultaneously exposed to risk, they fail independently of each other. Moreover, the failure rate of a part at any given instant when it is exposed to risk does not depend on the particular machine in which the part is installed nor on the sequence of machines through which it has passed.

⁷The terms "synchronous clocks" and "asynchronous clocks" are motivated by the following interpretation: We imagine that each part is equipped with its own clock, all clocks being set to 0 and turned on at time 0. Under the assumption of synchronous clocks, no clock is ever turned off. Under the assumption of asynchronous clocks, the clock associated with a given part is turned off when the part is not engaged; hence, under this assumption two operational parts, one of which is in state $(0,1)$ during the time interval $[(k-1)\tau, k\tau]$ and the other of which is in state $(1,1)$ during this time interval, will, at time $k\tau$, have clocks showing different times if at time $(k-1)\tau$ they showed the same time.

3. THE CASE OF SYNCHRONOUS CLOCKS

In this section we restrict attention to the case of synchronous clocks. Suppose that at the time $k\tau$, when the $(k+1)$ -st mission is dispatched, there are S_i operational parts of type i , $i = 1, 2, \dots, r$. Setting

$$\phi = \min_{1 \leq i \leq r} S_i ,$$

it is clear that by appropriate cannibalizations exactly ϕ machines can be assembled, all of whose parts are operational. It therefore seems reasonable to define ϕ to be the "performance level" of the system at time $k\tau$.

We now associate to each part γ_{ij} a random variable X_{ij} , called the "lifetime" of γ_{ij} , whose value denotes the time of failure of γ_{ij} . We shall assume that each random variable X_{ij} is exponentially distributed with distribution function

$$P\{X_{ij} < t\} = \begin{cases} 1 - e^{-\alpha_i t} , & t > 0 , \\ 0 & , \quad t \leq 0 . \end{cases}$$

We emphasize that the failure rate α_i of γ_{ij} depends only on the part type i . Clearly the expected lifetime of a part of type i is

$$E[X_{ij}] = \alpha_i^{-1} > 0 .$$

Under the assumption of independent failures (stated in Section 1) it follows that the random variables $(X_{ij})_{\substack{i=1,2,\dots,r \\ j=1,2,\dots,n}}$ are independent.

We obtain a convenient expression for the number of operational parts of each type at time $k\tau$ by introducing the indicators $Y_{ij}(k)$ of the events $\{X_{ij} \geq k\tau\}$, defined for $k \geq 0$ and the admissible values of i, j by the equations

$$Y_{ij}(k) = \begin{cases} 1, & \text{if } X_{ij} \geq k\tau, \\ 0, & \text{otherwise.} \end{cases}$$

Plainly, for each index k the random variables $(Y_{ij}(k))_{\substack{i=1,2,\dots,r \\ j=1,2,\dots,n}}$ are independent, and

$$(1) \quad Y_{ij}(k) = \begin{cases} 1, & \text{with probability } e^{-\alpha_i k\tau}, \\ 0, & \text{with probability } 1 - e^{-\alpha_i k\tau}. \end{cases}$$

Let

$$(2) \quad S_{in}(k) = \sum_{j=1}^n Y_{ij}(k).$$

Then $S_{in}(k)$ denotes the number of operational parts of type i at time $k\tau$, given that the size of the system is n . Setting

$$p_i(k) = e^{-\alpha_i k\tau}$$

and

$$q_i(k) = 1 - p_i(k),$$

it follows from (1) and (2) and the independence of $(Y_{ij}(k))_{j=1,2,\dots,n}$ that

$$(3) \quad P\{S_{in}(k) = m\} = \binom{n}{m} p_i^m(k) q_i^{n-m}(k), \quad m = 0, 1, \dots, n.$$

By definition, the system performance level at time $k\tau$ is given by the random variable

$$\Phi_n(k) = \min_{1 \leq i \leq r} S_{in}(k)$$

We observe now that for each pair of indices (n, k) the random variables $S_{1n}(k), S_{2n}(k), \dots, S_{rn}(k)$ are independent, since the random vectors

$$(Y_{11}(k), Y_{12}(k), \dots, Y_{1n}(k)), (Y_{21}(k), Y_{22}(k), \dots, Y_{2n}(k)), \\ \dots, (Y_{r1}(k), Y_{r2}(k), \dots, Y_{rn}(k)))$$

are independent. Hence, the expected performance level at time kt can be determined from the tail distribution by the well-known formula,

$$\begin{aligned} (4) \quad E[\phi_n(k)] &= \sum_{\lambda=0}^{n-1} P\{\phi_n(k) > \lambda\} \\ &= \sum_{\lambda=0}^{n-1} P\{S_{1n}(k) > \lambda, S_{2n}(k) > \lambda, \dots, S_{rn}(k) > \lambda\} \\ &= \sum_{\lambda=0}^{n-1} \prod_{i=1}^r P\{S_{in}(k) > \lambda\} = \sum_{\lambda=0}^{n-1} \prod_{i=1}^r \sum_{m=\lambda+1}^n \binom{n}{m} p_i^m(k) q_i^{n-m}(k) \\ &= \sum_{\lambda=1}^n \prod_{i=1}^r \sum_{m=\lambda}^n \binom{n}{m} p_i^m(k) q_i^{n-m}(k) \cdot^8 \end{aligned}$$

It follows immediately from the definition of $\phi_n(k)$ that the expected system performance level is, for fixed k , an increasing function of n , i.e.,

$$E[\phi_{n+1}(k)] \geq E[\phi_n(k)], \quad n = 1, 2, \dots$$

⁸This formula is a special case of equations (4.3) and (4.4) in [1], which give the expected performance level of an arbitrary system subject to cannibalization.

Enlarging the size of the system, however, entails added cost, and it is therefore of interest to introduce some measure of the return per dollar of investment. To this end we define the "efficiency" $\rho_n(k)$ of a system after k missions, given that the system has size n , as the expected performance per machine; thus,

$$(5) \quad \rho_n(k) = \frac{1}{n} E[\Phi_n(k)] .$$

We emphasize that, in general, the efficiency depends not only on the time $k\tau$ at which it is evaluated but also on the size, n , of the system. It is of interest to study the behavior of $\rho_n(k)$ as n varies and to compare the efficiencies of cannibalized and uncannibalized systems.

Let us consider the system described in Section 1, assuming that cannibalizations are not performed. Let $\Phi_n^O(k)$ and $\rho_n^O(k)$ denote, respectively, the performance level and efficiency after k missions, given that the system has size n . Since a given machine will be operational at time $k\tau$ if and only if all of its parts survive k missions, and this occurs with probability $p_1(k)p_2(k)\cdots p_r(k)$, it is clear that

$$P\{\Phi_n^O(k)=m\} = \binom{n}{m} [p_1(k)p_2(k)\cdots p_r(k)]^m [1-p_1(k)p_2(k)\cdots p_r(k)]^{n-m}.$$

Hence, by an elementary formula,

$$E[\Phi_n^O(k)] = np_1(k)p_2(k) \cdots p_r(k) ,$$

and

$$(6) \quad \rho_n^c(k) = p_1(k) p_2(k) \cdots p_r(k) .$$

From (4) and (5) we see that the efficiency of the system when cannibalisation is practiced is given by the expression

$$(7) \quad \rho_n(k) = \frac{1}{n} \sum_{\lambda=1}^n \prod_{i=1}^r \sum_{m=\lambda}^n \binom{n}{m} p_i^m(k) q_i^{n-m}(k) .$$

We note from (6) that the efficiency of the uncannibalized system is a constant depending only on the part failure rates and is independent of the system size, whereas from (7) it is clear that the efficiency of the cannibalized system varies with n , although it is by no means obvious precisely how the efficiency changes as the system is enlarged.

The tables in the Appendix show how the efficiencies of the cannibalized and uncannibalized systems compare in various special cases. These tables suggest that for each fixed time kt the efficiency of the cannibalized system is a strictly increasing function of the system size. For simplicity we present here a proof of this result only in a very special case, leaving for another paper a discussion of the full theorem.

THEOREM 1. Let $\rho_n(k)$ denote the efficiency after k missions of the system described in Section 1, assuming that cannibalization is practiced, each machine is composed of two parts, the failure rates of the parts are equal, and clocks are synchronous. Then for each positive integer k ,

$$\rho_n(k) < \rho_{n+1}(k) , \quad n = 1, 2, \dots .$$

Proof. Since k will be held fixed throughout our argument, for simplicity we suppress k in all our notation. From the definition of efficiency,

$$(8) \quad \rho_{n+1} - \rho_n = E \left[\frac{\phi_{n+1}}{n+1} - \frac{\phi_n}{n} \right] = \frac{1}{n(n+1)} E[n(\phi_{n+1} - \phi_n) - \phi_n] .$$

Setting

$$\phi_0 = 0$$

and

$$\Delta_n = \phi_{n+1} - \phi_n , \quad n = 0, 1, \dots ,$$

from (8) we see that it suffices to prove

$$(9) \quad E[n\Delta_n - \phi_n] > 0 , \quad n = 1, 2, \dots .$$

Writing ϕ_n in the form

$$\phi_n = \sum_{j=0}^{n-1} \Delta_j , \quad n = 1, 2, \dots ,$$

inequality (9) reduces to

$$(10) \quad E[n\Delta_n] - \sum_{j=0}^{n-1} E[\Delta_j] > 0 , \quad n=1, 2, \dots .$$

We define for $n \geq 1$,

$$(11) \quad u_n = P\{S_{1n} = S_{2n}\} .$$

It is convenient to introduce the additional definition,

$$u_0 = 1 .$$

Setting

$$p_1(k) = p_2(k) = p ,$$

it is easy to verify that for $n \geq 0$, Δ_n takes only the values 1, 0 with, respectively, the probabilities

$$P\{\Delta_n=1\} = u_n p^2 + (1-u_n)p ,$$

$$P\{\Delta_n=0\} = 1 - [u_n p^2 + (1-u_n)p] .$$

Since $E[\Delta_n] = P\{\Delta_n=1\}$, (10) is equivalent to the inequality

$$n[u_n p^2 + (1-u_n)p] - \sum_{j=0}^{n-1} [u_j p^2 + (1-u_j)p] > 0 ,$$

which in turn reduces to

$$(12) \quad p(1-p) \left(n u_n - \sum_{j=0}^{n-1} u_j \right) < 0 .$$

By Abel's partial summation formula,

$$n u_n - \sum_{j=0}^{n-1} u_j = \sum_{j=1}^n j(u_j - u_{j-1}) .$$

Since $p(1-p) > 0$, to prove (12) it suffices to establish the inequality

$$(13) \quad \sum_{j=1}^n j(u_j - u_{j-1}) < 0 .$$

We shall in fact prove the stronger result that for all positive integers j ,

$$(14) \quad u_j < u_{j-1} .$$

To this end we note from (3), (11), and the independence of the random variables S_{1n}, S_{2n} that

$$u_n = \sum_{m=0}^n \binom{n}{m}^2 p^{2m} (1-p)^{2(n-m)} , \quad n = 0, 1, \dots .$$

Let us recall that if f is the polynomial

$$f(z) = \sum_{m=0}^j a_m z^m ,$$

then

$$(15) \quad \frac{1}{2\pi} \int_0^{2\pi} f(e^{i\theta}) \bar{f}(e^{i\theta}) d\theta = \frac{1}{2\pi} \int_0^{2\pi} |f(e^{i\theta})|^2 d\theta = \sum_{m=0}^j |a_m|^2 .$$

Setting $q = 1-p$ and applying (15) to the particular function

$$f(z) = (p+qz)^j = \sum_{m=0}^j \binom{j}{m} p^m q^{j-m} z^{j-m} ,$$

we obtain

$$(16) \quad \frac{1}{2\pi} \int_0^{2\pi} |p+qe^{i\theta}|^{2j} d\theta = \sum_{m=0}^j \binom{j}{m}^2 p^{2m} q^{2(j-m)} = u_j .$$

Now noting that for $0 < \theta < 2\pi$,

$$|p+qe^{i\theta}|^2 < p+q = 1 ,$$

and for $\theta = 0$ or 2π ,

$$|p+qe^{i\theta}|^2 = 1 ,$$

(14) follows from (16). This completes the proof of the theorem.

A measure of the advantages of practicing cannibalization on a system of size n during a time period of duration $k\tau$ is given by the ratio of efficiencies

$$\mu_n(k) = \frac{\rho_n(k)}{\rho_n^0(k)} .$$

The limit

$$(17) \quad \mu_\infty(k) = \lim_{n \rightarrow \infty} \mu_n(k) ,$$

if it exists, can be interpreted as a measure of the advantage of cannibalizing a very large system in the time interval $[0, k\tau]$. We call $\mu_\infty(k)$ the "maintenance index for k missions." The limit

$$\mu^* = \lim_{k \rightarrow \infty} \mu_\infty(k) ,$$

if it exists, is called the "steady state maintenance index"; it provides an estimate of the long-run superiority of a very large cannibalized system over an uncannibalized one.

THEOREM 2. In the case of synchronous clocks, the maintenance indices of the system described in Section 1 satisfy the equations

$$(18) \quad \mu_\infty(k) = \frac{\min_{1 \leq i \leq r} p_i(k)}{p_1(k)p_2(k) \cdots p_r(k)}$$

and

$$(19) \quad \mu^* = \infty .$$

Proof. By the Strong Law of Large Numbers,

$$\lim_{n \rightarrow \infty} \frac{1}{n} S_{in}(k) = p_i(k) \quad \text{a.s.}, \quad i = 1, 2, \dots, r.$$

Consequently,

$$\lim_{n \rightarrow \infty} \frac{\Phi_n(k)}{n} = \lim_{n \rightarrow \infty} \min_{1 \leq i \leq r} \frac{1}{n} S_{in}(k) = \min_{1 \leq i \leq r} p_i(k) \quad \text{a.s.}$$

Since $|\frac{1}{n} \Phi_n(k)| \leq 1$, by the Lebesgue bounded convergence theorem it follows that

$$\lim_{n \rightarrow \infty} E[\frac{1}{n} \Phi_n(k)] = \min_{1 \leq i \leq r} p_i(k) .$$

Hence, using (6), we have

$$\mu_{\infty}(k) = \frac{\min_{1 \leq i \leq r} p_i(k)}{p_1(k)p_2(k) \cdots p_r(k)} ,$$

which, from the definition of $p_i(k)$, reduces to

$$\mu_{\infty}(k) = \left(\frac{\min_{1 \leq i \leq r} e^{-\alpha_i \tau}}{e^{-\sum_{i=1}^r \alpha_i \tau}} \right)^k .$$

Since

$$\frac{\min_{1 \leq i \leq r} e^{-\alpha_i \tau}}{e^{-\sum_{i=1}^r \alpha_i \tau}} = \min_{1 \leq i \leq r} e^{-\alpha_i \tau} e^{\sum_{i=1}^r \alpha_i \tau} > 1 ,$$

we have

$$\lim_{k \rightarrow \infty} \mu_{\infty}(k) = \infty ,$$

which completes the proof.

3. THE CASE OF ASYNCHRONOUS CLOCKS

The case of asynchronous clocks, although more realistic, is analytically more complicated because the lifetimes

$(X_{ij})_{\substack{i=1,2,\dots,r \\ j=1,2,\dots,n}}$ are no longer independent random variables.

We confine ourselves in this case to showing that the maintenance indices are precisely the same as they are in the case dealt with in the previous section.

THEOREM 3. In the case of asynchronous clocks, the maintenance indices of the system described in Section 1 satisfy the equations

$$\mu_{\infty}(k) = \frac{\min_{1 \leq i \leq r} p_i(k)}{p_1(k)p_2(k) \cdots p_r(k)}$$

and

$$\mu^* = \infty.$$

Proof. Let $(X_{ij}(k))_{\substack{i=1,2,\dots,r \\ j=1,2,\dots,n \\ k=1,2,\dots}}$ be a family of random variables

such that for each k the random variables $(X_{ij}(k))_{\substack{i=1,2,\dots,r \\ j=1,2,\dots,n}}$ are independent, and for all i, j, k ,

$$X_{ij}(k) = \begin{cases} 1, & \text{with probability } p_i(1), \\ 0, & \text{with probability } 1-p_i(1). \end{cases}$$

The random variable $X_{ij}(1)$ corresponds to a part of type i used on the first mission; $X_{ij}(1) = 1$ if and only if the part to which

it corresponds survives the first mission. Thus, the random variable $\sum_{j=1}^n X_{ij}(1)$ denotes the number of parts of type i operational at the outset of the second mission, and the random variable

$$(20) \quad N_1 = N_1(n) = \min_{1 \leq i \leq r} \sum_{j=1}^n X_{ij}(1)$$

denotes the number of operational machines obtained by cannibalization after the first mission. For each fixed index i the random variables $X_{ij}(2)$, $j = 1, 2, \dots, N_1$, correspond to the N_1 parts of type i used on the second mission; $X_{ij}(2) = 1$ if and only if the part to which it corresponds survives the second mission. The assumed independence of the random variables $(X_{ij}(2))_{\substack{i=1,2,\dots,r \\ j=1,2,\dots,n}}$ reflects the fact that when parts are simultaneously exposed to risk, they fail independently of each other. Clearly the number of operational parts of type i available after the second mission consists of parts of type i dispatched on the second mission that survive the second mission, i.e., $\sum_{j=1}^{N_1} X_{ij}(2)$, plus parts of type i that survived the first mission but were not used on the second, i.e., $\sum_{j=1}^n X_{ij}(1) - N_1$. Thus, the number of operational machines obtained by cannibalization after the second mission is given by the random variable

$$(21) \quad N_2 = N_2(n) = \min_{1 \leq i \leq r} \left[\sum_{j=1}^n X_{ij}(1) + \sum_{j=1}^{N_1} X_{ij}(2) - N_1 \right].$$

More generally, we define recursively a sequence of random variables

$$N_1, N_2, \dots$$

by choosing N_1 according to (20); then, assuming N_1, N_2, \dots, N_{k-1}

have been defined, we set

$$(22) \quad N_k = N_k(n) = \min_{1 \leq i \leq r} \left[\sum_{j=1}^n X_{ij}(1) + \sum_{j=1}^{N_1} X_{ij}(2) \right. \\ \left. + \dots + \sum_{j=1}^{N_{k-1}} X_{ij}(k) - \sum_{v=1}^{k-1} N_v \right].$$

By an argument similar to the one used in deriving (21) it follows that N_k is the number of operational machines obtained by cannibalization after the k -th mission, i.e., it is the system performance level at time $k\tau$.

To obtain the maintenance index for k missions we shall prove inductively that for all integers k ,

$$(23) \quad \lim_{n \rightarrow \infty} \frac{1}{n} N_k(n) = \min_{1 \leq i \leq r} p_i(k).$$

To shorten notation we set

$$p_i = p_i(1) = e^{-\alpha_i \tau}$$

and

$$\delta = \min_{1 \leq i \leq r} p_i > 0.$$

By the Strong Law of Large Numbers,

$$\lim_{n \rightarrow \infty} \frac{1}{n} \sum_{j=1}^n X_{ij}(1) = p_i \quad \text{a.s.}$$

Hence,

$$(24) \quad \lim_{n \rightarrow \infty} \frac{1}{n} N_1(n) = \delta \quad \text{a.s.,}$$

i.e.,

$$N_1(n) \sim n\delta \quad \text{a.s.}$$

Assume that for $v \leq k-1$,

$$N_v(n) \sim n\delta^v, \text{ a.s.}$$

Since this implies that $N_v(n) \rightarrow \infty$ as $n \rightarrow \infty$, we obtain from the Strong Law of Large Numbers the relation

$$\lim_{n \rightarrow \infty} \frac{1}{n} \sum_{j=1}^{N_v} X_{ij}(v+1) = \lim_{n \rightarrow \infty} \frac{N_v}{n} \frac{1}{N_v} \sum_{j=1}^{N_v} X_{ij}(v+1) = \delta^v p_i, \text{ a.s.}$$

Hence, we conclude from (22) that a.s.

$$\begin{aligned} \lim_{n \rightarrow \infty} \frac{1}{n} N_k(n) &= \min_{1 \leq i \leq r} (p_i + \delta p_i + \dots + \delta^{k-1} p_i - \sum_{v=1}^{k-1} \delta^v) \\ &= \min_{1 \leq i \leq r} (p_i \sum_{j=0}^{k-1} \delta^j - \sum_{v=1}^{k-1} \delta^v) \\ &= (\sum_{j=0}^{k-1} \delta^j) (\min_{1 \leq i \leq r} p_i) - \sum_{v=1}^{k-1} \delta^v \\ &= \sum_{j=1}^k \delta^j - \sum_{v=1}^{k-1} \delta^v = \delta^k. \end{aligned}$$

This completes the induction. Since

$$\delta^k = (\min_{1 \leq i \leq r} p_i(1))^k = (\min_{1 \leq i \leq r} e^{-\alpha_i \tau})^k = \min_{1 \leq i \leq r} e^{-\alpha_i k \tau} = \min_{1 \leq i \leq r} p_i(k),$$

(23) is proved. From the definition of N_k it is obvious that

$|\frac{N_k}{n}| \leq 1$, so that by the Lebesgue bounded convergence theorem,

$$\lim_{n \rightarrow \infty} \frac{1}{n} \text{EIN}_K(n) = \lim_{n \rightarrow \infty} \rho_n(k) = \min_{1 \leq i \leq r} \rho_i(k) .$$

Plainly, the efficiency of the uncannibalized system after k missions does not depend on whether or not clocks are synchronous. It follows that the maintenance indices are the same as in Theorem 2.

Acknowledgment: We should like to acknowledge that our interest in the subject matter of this paper was stimulated by results of A. J. Rolfe [2], whose numerical computations suggested the validity of the theorems we have proved. We are indebted also to Professor Agnes Berger for many stimulating discussions in connection with Theorem 1.

APPENDIX

TABLE 1

Efficiency After k Missions of a System with 2 Part Types

System Sizes, 2-13

$$p_1(1) = .9, p_2(1) = .95$$

No. of Mis. k	Cannibalized System of Size												Uncan. System of Any Size
	2	3	4	5	6	7	8	9	10	11	12	13	
1	.859	.863	.866	.869	.871	.873	.875	.877	.878	.880	.881	.882	.855
2	.745	.755	.763	.769	.774	.778	.781	.784	.786	.788	.790	.791	.731
3	.649	.665	.676	.685	.691	.696	.700	.703	.706	.708	.710	.712	.625
4	.568	.589	.602	.612	.619	.624	.628	.632	.634	.637	.639	.640	.534
5	.499	.523	.537	.547	.554	.560	.564	.568	.570	.573	.575	.576	.457
6	.439	.464	.479	.490	.497	.502	.507	.510	.513	.515	.517	.519	.391
7	.387	.412	.428	.438	.446	.451	.455	.459	.461	.464	.465	.467	.334
8	.340	.366	.382	.392	.399	.405	.409	.412	.415	.417	.419	.420	.286
9	.299	.326	.341	.351	.358	.363	.367	.370	.373	.375	.377	.378	.245
10	.263	.289	.304	.314	.321	.326	.330	.333	.335	.337	.339	.340	.209
11	.231	.256	.271	.281	.287	.292	.296	.299	.301	.303	.305	.306	.179
12	.203	.227	.241	.251	.257	.262	.266	.269	.271	.273	.274	.275	.153
13	.178	.201	.215	.224	.230	.235	.238	.241	.243	.245	.246	.247	.131
14	.156	.178	.191	.200	.206	.210	.214	.216	.218	.220	.221	.222	.112
15	.136	.157	.170	.178	.184	.188	.192	.194	.196	.198	.199	.200	.096

TABLE 2

Efficiency after k Missions of a System with 7 Part Types

System Sizes, 14-25

$$p_1(1) = .9, p_2(1) = .95$$

No. of Mis. k	Cannibalized System of Size												Uncan. System of Any Size
	14	15	16	17	18	19	20	21	22	23	24	25	
1	.883	.884	.885	.886	.886	.887	.888	.888	.889	.889	.890	.890	.855
2	.793	.794	.795	.796	.797	.798	.798	.799	.800	.800	.801	.801	.731
3	.713	.715	.716	.717	.718	.718	.719	.720	.720	.721	.722	.722	.625
4	.642	.643	.644	.645	.646	.647	.648	.648	.649	.650	.650	.651	.534
5	.578	.579	.580	.581	.582	.583	.584	.584	.585	.585	.586	.586	.457
6	.520	.521	.523	.523	.524	.525	.526	.526	.527	.527	.527	.528	.391
7	.468	.469	.470	.471	.472	.473	.473	.474	.474	.475	.475	.475	.334
8	.422	.423	.423	.424	.425	.426	.426	.427	.427	.427	.428	.428	.286
9	.379	.380	.381	.382	.382	.383	.384	.384	.384	.385	.385	.385	.245
10	.341	.342	.343	.344	.344	.345	.345	.346	.346	.346	.347	.347	.209
11	.307	.308	.309	.309	.310	.310	.311	.311	.311	.312	.312	.312	.179
12	.276	.277	.278	.278	.279	.279	.280	.280	.280	.281	.281	.281	.153
13	.248	.249	.250	.250	.251	.251	.252	.252	.252	.252	.253	.253	.131
14	.223	.224	.225	.225	.226	.226	.226	.227	.227	.227	.227	.228	.113
15	.201	.202	.202	.203	.203	.203	.204	.204	.204	.204	.205	.205	.096

TABLE 3

Efficiency after k Missions of a System with 3 Part Types

System Sizes, 2-13

$$p_1(1) = .9, p_2(1) = .92, p_3(1) = .96$$

No. of Mis. k	Cannibalized System of Size												Uncan. System of Any Size
	2	3	4	5	6	7	8	9	10	11	12	13	
1	.807	.817	.825	.832	.837	.842	.846	.850	.853	.856	.858	.860	.795
2	.667	.691	.709	.721	.731	.738	.744	.749	.754	.757	.761	.763	.632
3	.561	.595	.617	.632	.643	.652	.659	.665	.670	.674	.677	.680	.502
4	.476	.515	.540	.556	.568	.577	.585	.591	.596	.600	.604	.607	.399
5	.406	.448	.473	.490	.502	.512	.519	.525	.531	.535	.539	.542	.317
6	.346	.389	.414	.431	.444	.454	.461	.467	.473	.477	.481	.484	.252
7	.295	.337	.363	.380	.392	.402	.410	.416	.421	.425	.429	.432	.200
8	.250	.292	.317	.334	.347	.356	.364	.370	.375	.379	.383	.386	.159
9	.212	.253	.277	.294	.306	.315	.323	.329	.334	.338	.341	.344	.126
10	.179	.218	.242	.258	.270	.279	.286	.292	.297	.301	.304	.307	.100
11	.150	.188	.211	.226	.238	.247	.253	.259	.264	.268	.271	.274	.080
12	.126	.161	.183	.198	.209	.218	.224	.230	.234	.238	.241	.244	.064
13	.105	.138	.159	.173	.184	.192	.198	.203	.208	.211	.215	.217	.051
14	.087	.118	.137	.151	.161	.169	.175	.180	.184	.188	.191	.193	.041
15	.072	.100	.118	.131	.141	.148	.154	.159	.163	.166	.169	.172	.033

TABLE 4

Efficiency After k Missions of a System with 3 Part Types

System Sizes, 14-25

$$p_1(1) = .9, p_2(1) = .92, p_3(1) = .96$$

No. of Mis. k	Cannibalized System of Size												Uncan. System of Any Size
	14	15	16	17	18	19	20	21	22	23	24	25	
1	.862	.864	.865	.867	.868	.869	.870	.871	.872	.873	.874	.875	.795
2	.766	.768	.770	.772	.773	.775	.776	.778	.779	.780	.781	.782	.632
3	.683	.685	.688	.690	.691	.693	.695	.696	.697	.698	.699	.700	.502
4	.610	.613	.615	.617	.619	.620	.622	.623	.625	.626	.627	.628	.399
5	.545	.548	.550	.552	.554	.556	.557	.559	.560	.561	.562	.563	.317
6	.487	.490	.492	.494	.496	.498	.499	.500	.502	.503	.504	.505	.252
7	.435	.438	.440	.442	.444	.446	.447	.448	.450	.451	.452	.453	.200
8	.389	.391	.393	.395	.397	.399	.400	.402	.403	.404	.405	.406	.159
9	.347	.350	.352	.354	.355	.357	.358	.360	.361	.362	.363	.364	.126
10	.310	.312	.314	.316	.318	.319	.321	.322	.323	.324	.325	.326	.100
11	.276	.279	.281	.283	.284	.286	.287	.288	.289	.291	.292	.292	.080
12	.246	.249	.251	.252	.254	.255	.257	.258	.259	.260	.261	.262	.064
13	.220	.222	.224	.225	.227	.228	.229	.231	.232	.233	.234	.234	.051
14	.196	.198	.199	.201	.202	.204	.205	.206	.207	.208	.209	.210	.041
15	.174	.176	.178	.179	.181	.182	.183	.184	.185	.186	.187	.188	.033

TABLE 5

Efficiency After k Missions of a System with 4 Part Types

System Sizes, 2-13

$$p_1(1) = .9, p_2(1) = .92, p_3(1) = .95, p_4(1) = .97$$

No. of Mis. k	Cannibalized System of Size												Uncan. System of Any Size
	2	3	4	5	6	7	8	9	10	11	12	13	
1	.781	.796	.808	.817	.825	.831	.837	.841	.845	.849	.852	.854	.763
2	.634	.668	.690	.706	.718	.728	.735	.741	.746	.751	.754	.758	.582
3	.527	.572	.600	.618	.632	.642	.650	.657	.663	.668	.672	.675	.444
4	.444	.494	.523	.543	.557	.568	.577	.584	.590	.595	.599	.603	.339
5	.375	.427	.457	.477	.492	.503	.512	.519	.525	.530	.534	.538	.259
6	.318	.369	.399	.419	.434	.445	.454	.461	.467	.473	.477	.481	.198
7	.268	.318	.348	.368	.383	.394	.403	.410	.416	.421	.425	.429	.151
8	.224	.274	.304	.324	.338	.349	.358	.365	.370	.375	.379	.383	.115
9	.187	.235	.264	.284	.298	.309	.317	.324	.329	.334	.338	.342	.088
10	.155	.202	.230	.249	.262	.273	.281	.287	.293	.297	.301	.305	.067
11	.128	.172	.199	.217	.230	.241	.248	.255	.260	.265	.268	.272	.051
12	.105	.146	.172	.190	.202	.212	.220	.226	.231	.235	.239	.242	.039
13	.085	.124	.148	.165	.177	.186	.194	.200	.205	.209	.212	.215	.030
14	.069	.104	.127	.143	.155	.164	.171	.176	.181	.185	.188	.191	.023
15	.056	.087	.109	.124	.135	.143	.150	.156	.160	.164	.167	.170	.018

TABLE C

Efficiency After k Missions of a System with 4 Part Types

System Sizes, 14-25

$$p_1(1) = .9, p_2(1) = .92, p_3(1) = .95, p_4(1) = .97$$

No. of Mis. k	Cannibalized System of Size												Uncan. System of Any Size
	14	15	16	17	18	19	20	21	22	23	24	25	
1	.856	.859	.860	.862	.864	.865	.866	.868	.869	.870	.871	.872	.763
2	.761	.763	.766	.768	.770	.771	.773	.774	.776	.777	.778	.779	.582
3	.678	.681	.684	.686	.688	.690	.692	.693	.695	.696	.697	.698	.444
4	.606	.609	.611	.614	.616	.618	.620	.621	.623	.624	.625	.626	.339
5	.541	.544	.547	.549	.551	.553	.555	.557	.558	.559	.561	.562	.259
6	.484	.487	.489	.492	.494	.496	.497	.499	.500	.502	.503	.504	.198
7	.432	.435	.438	.440	.442	.444	.446	.447	.448	.450	.451	.452	.151
8	.386	.389	.391	.394	.396	.397	.399	.401	.402	.403	.404	.405	.115
9	.345	.347	.350	.352	.354	.356	.357	.359	.360	.361	.362	.363	.088
10	.308	.310	.313	.315	.317	.318	.320	.321	.322	.324	.325	.326	.067
11	.274	.277	.279	.281	.283	.285	.286	.287	.289	.290	.291	.292	.05;
12	.245	.247	.249	.251	.253	.254	.256	.257	.258	.259	.260	.261	.039
13	.218	.220	.222	.224	.226	.227	.229	.230	.231	.232	.233	.234	.030
14	.194	.196	.198	.200	.201	.203	.204	.205	.207	.208	.209	.209	.023
15	.172	.174	.176	.178	.180	.181	.182	.184	.185	.186	.186	.187	.018

TABLE 7

Efficiency After k Missions of a System with 5 Part Types

System Sizes, 2-13

$$p_1(1) = .9, p_2(1) = .92, p_3(1) = .95, p_4(1) = .97, p_5(1) = .99$$

No. of Mis. k	Cannibalized System of Size												Uncan. System of Any Size
	2	3	4	5	6	7	8	9	10	11	12	13	
1	.775	.791	.804	.814	.823	.830	.835	.840	.844	.848	.851	.854	.755
2	.627	.663	.688	.705	.717	.727	.735	.741	.746	.750	.754	.758	.570
3	.521	.569	.598	.617	.631	.641	.650	.657	.663	.667	.672	.675	.430
4	.439	.491	.522	.542	.556	.568	.576	.584	.589	.595	.599	.603	.325
5	.371	.425	.456	.476	.491	.503	.512	.519	.525	.530	.534	.538	.245
6	.314	.367	.398	.419	.434	.445	.454	.461	.467	.472	.477	.481	.185
7	.265	.317	.348	.368	.383	.394	.403	.410	.416	.421	.425	.429	.140
8	.222	.273	.303	.323	.338	.349	.358	.365	.370	.375	.379	.383	.106
9	.185	.235	.264	.284	.298	.309	.317	.324	.329	.334	.338	.342	.080
10	.153	.201	.229	.248	.262	.273	.281	.287	.293	.297	.301	.305	.060
11	.126	.172	.199	.217	.230	.240	.248	.255	.260	.265	.268	.272	.045
12	.103	.146	.172	.189	.202	.212	.219	.226	.231	.235	.239	.242	.034
13	.084	.123	.148	.165	.177	.186	.194	.200	.205	.209	.212	.215	.026
14	.068	.104	.127	.143	.155	.164	.171	.176	.181	.185	.188	.191	.020
15	.055	.087	.109	.124	.135	.143	.150	.156	.160	.164	.167	.170	.015

TABLE 8

Efficiency After k Missions of a System with 5 Part Types

System Sizes, 14-25

$$p_1(1) = .9, p_2(1) = .92, p_3(1) = .95, p_4(1) = .97, p_5(1) = .99$$

No. of Mis. k	Cannibalized System of Size												Uncan. System of Any Size
	14	15	16	17	18	19	20	21	22	23	24	25	
1	.856	.858	.860	.862	.863	.865	.866	.867	.869	.870	.871	.871	.755
2	.761	.763	.766	.768	.770	.771	.773	.774	.776	.777	.778	.779	.570
3	.678	.681	.684	.686	.688	.690	.692	.693	.695	.696	.697	.698	.430
4	.606	.609	.611	.614	.616	.618	.620	.621	.623	.624	.625	.626	.325
5	.541	.544	.547	.549	.551	.553	.555	.557	.558	.559	.561	.562	.245
6	.484	.487	.489	.492	.494	.496	.497	.499	.500	.502	.503	.504	.185
7	.432	.435	.438	.440	.442	.444	.446	.447	.448	.450	.451	.452	.140
8	.386	.389	.391	.394	.396	.397	.399	.401	.402	.403	.404	.405	.106
9	.345	.347	.350	.352	.354	.356	.357	.359	.360	.361	.362	.363	.080
10	.308	.310	.313	.315	.317	.318	.320	.321	.322	.324	.325	.326	.060
11	.274	.277	.279	.281	.283	.285	.286	.287	.289	.290	.291	.292	.045
12	.245	.247	.249	.251	.253	.254	.256	.257	.258	.259	.260	.261	.034
13	.218	.220	.222	.224	.226	.227	.229	.230	.231	.232	.233	.234	.026
14	.194	.196	.198	.200	.201	.203	.204	.205	.207	.208	.209	.209	.020
15	.172	.174	.176	.178	.180	.181	.182	.184	.185	.186	.186	.187	.015

REFERENCES

1. Hirsch, Warren M., Meisner, Morris, and Boll, Charles, 1968.
Cannibalization in multicomponent systems and the theory
of reliability. Nav. Res. Log. Qu. Vol. 15, No. 3.
2. Rolfe, Alan, J., 1970. Markov chain analysis of a situation
where cannibalization is the only repair activity.
Nav. Res. Log. Qu. 17, Vol. 17, No. 2.

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) New York University Courant Institute of Mathematical Sciences		2a. REPORT SECURITY CLASSIFICATION not classified	
		2b. GROUP none	
3. REPORT TITLE Asymptotic Performance of a System Subject to Cannibalization			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Technical Report May 1970			
5. AUTHOR(S) (Last name, first name, initial) Hirsch, Warren M. and Hanisch, Herman			
6. REPORT DATE May 1970		7a. TOTAL NO. OF PAGES 29	7b. NO. OF REFS 2
8a. CONTRACT OR GRANT NO. N00014-67-A-0467-0004		9a. ORIGINATOR'S REPORT NUMBER(S) IMM 382	
b. PROJECT NO. NR 042-206			
c.		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
d.		none	
10. AVAILABILITY/LIMITATION NOTICES Distribution of this document is unlimited.			
11. SUPPLEMENTARY NOTES none		12. SPONSORING MILITARY ACTIVITY U.S. Navy, Office of Naval Research 207 West 24th St., New York, N.Y.	
13. ABSTRACT We consider the performance of a system composed of n machines, each machine being composed of parts (or modules) of r different types arranged in a series. If S_i denotes the number of parts of type i functioning at a given moment, it is assumed that the performance level, Φ , of the overall system at that moment is given by the equation $\Phi = \min_{1 \leq i \leq r} S_i .$ A collection of identical structures (ships, aircraft, missile batteries, etc.) exemplifies the kind of system we have in mind, under the simplifying assumption that each part in a given structure is essential to the performance of that structure. Limit theorems			

14 KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, roles, and weights is optional.

13. Abstract - continued

are proved which make it possible to evaluate explicitly the asymptotic performance level of the system under three different assumptions:

1. Cannibalization is prohibited.
2. A failed part in a given machine can be replaced by an operating part of the same type taken from another machine. The lifetimes of the parts are mutually independent random variables.
3. A failed part in a given machine can be replaced by an operating part of the same type taken from another machine. Failures of parts may affect the lifetimes of other parts.

It is shown that assumptions (2) and (3) lead to asymptotically equivalent performance levels. The superiority of systems in which cannibalization is practiced over those in which it is prohibited is quantitatively appraised.

MASTER DISTRIBUTION LIST

NO0014-67A0467-0004

NOVEMBER 25, 1969

Head, Logistics and Mathematical (3)
Statistics Branch
Office of Naval Research
Washington, D.C. 20360

Commanding Officer
Office of Naval Research Branch (2)
Office
Navy #100 Fleet Post Office
New York, New York

Defense Documentation Center (20)
Cameron Station
Alexandria, Virginia 22314

Office of Naval Research (2)
Department of the Navy (Code 432)
Washington, D.C. 20360

Defense Logistics Studies
Information Exchange
Army Logistics Management Center
Fort Lee, Virginia
Attn: William B. Whichard

Office of Naval Research
495 Summer Street
Boston, Mass. 02210

Technical Information Officer (6)
Naval Research Laboratory
Washington, D.C. 20390

New York Area Office
Scientific Department
Office of Naval Research
207 West 24th Street
New York, New York 10011
Attn: J. Laderman

Commanding Office
Office of Naval Research Branch
Office
1030 East Green Street
Pasadena 1, California
Attn: Dr. A.R. Laufer

Bureau of Supplies and Accounts
Code OW
Department of the Navy
Washington 25, D.C.

Institute for Defense
Analyses
Communications Research
Division
von Neumann Hall
Princeton, New Jersey

University of Chicago
Statistical Research
Center
Chicago, Illinois
Attn: Professor Paul Meier

Stanford University
Applied Mathematics and
Statistics Lab.
Stanford, California
Attn: Prof. Gerald J.
Lieberman

Florida State University
Department of Statistics
Tallahassee, Florida
Attn: Dr. Ralph A. Bradley

Princeton University
Department of Mathematics
Princeton, New Jersey

Columbia University
Department of Mathematical
Statistics
New York 27, New York
Attn: Prof. T.W. Anderson

University of California
Department of Statistics
Berkeley 4, California
Attn: Prof. J. Neyman

University of Washington
Department of Mathematics
Seattle 5, Washington
Attn: Prof. Z.W. Birnbaum

Cornell University
Department of Mathematics
Ithaca, New York
Attn: Prof. J. Wolfowitz

Harvard University
Department of Statistics
Cambridge, Massachusetts
Attn: Prof. W.G. Cochran

The Research Triangle
Institute
Statistics Research Division
505 West Chapel Hill Street
Durham, North Carolina
Attn: Dr. Malcolm R. Leadbetter

Mass. Institute of
Technology
Department of Mathematics
Room 2-247
Cambridge, Mass. 02139

Columbia University
Department of Industrial
Engineering
New York 27, New York
Attn: Professor Cyrus Derman

Columbia University
Department of Mathematics
New York 27, New York
Attn: Professor H. Robbins

New York University
Courant Institute of
Mathematical Sciences
New York, New York 10012
Attn: Professor W.M. Hirsch

Cornell University
Department of Plant Breeding
Biometrics Unit
Ithaca, New York
Attn: Walter T. Federer

University of North Carolina
Statistics Department
Chapel Hill, North Carolina
Attn: Professor Walter L. Smith

Stanford University
Department of Statistics
Stanford, California
Attn: Professor Herman Rubin

Math Department
University of California
San Diego
LaJolla, California 92038
Attn: Professor M. Rosenblatt

New York University
Department of Industrial
Engineering and
Operations Research
Bronx 63, New York
Attn: Professor J.H. Kao

University of Wisconsin
Department of Statistics
Madison, Wisconsin
Attn: Professor G.E.P. Box

Yale University
Department of Mathematics
New Haven, Connecticut
Attn: Professor L.J. Savage

Stanford University
Institute in Engineering
and Economic Systems
School of Engineering
Stanford, California 94305
Attn: Dr. R.A. Howard

Stanford University
Department of Statistics
Stanford, California
Attn: Professor E. Parzen

Arcon Corporation
Box 419
Wakefield, Mass. 01880
Attn: Dr. Arthur Albert

University of California
Institute of Engineering
Research
Berkeley 4, California
Attn: Professor R.E. Barlow

Department of Probability
and Statistics
The University of Sheffield
Sheffield 10, England
Attn: Professor J. Gani

Professor Anders Hald
Institute of Mathematical
Statistics
University of Copenhagen
Copenhagen, Denmark

Dr. Jack R. Borsting
Chairman
Department of Operations
Analysis
U.S. Naval Postgraduate
School
Monterey, California 93940

Director
ONR Branch Office/Chicago
219 South Dearborn Street
Chicago, Ill. 60604

Professor Harold E. Dodge
Rutgers-The State University
Statistics Center
New Brunswick, New Jersey

Yale University
Department of Statistics
New Haven, Connecticut
Attn: Professor F.J. Anscombe

Purdue University
Division of Mathematical
Sciences
Lafayette, Indiana
Attn: Professor S.S. Gupta

Cornell University
Department of Industrial
Engineering
Ithaca, New York
Attn: Professor Robert Bechhofer

Stanford University
Department of Statistics
Stanford, California
Attn: Professor C. Stein

Applied Mathematics and
Statistics Lab.
Department of Statistics
Stanford University
Stanford, California
Attn: Professor H. Solomon

Decision Studies Group
845 Page Mill Road
Palo Alto, California
Attn: Warren R. Ketler

The Johns Hopkins University
Department of Mathematical
Statistics
34th and Charles Streets
Baltimore 18, Maryland
Attn: Professor Geoffrey S.
Watson

Office of Naval Research
San Francisco Area
50 Fell Street
San Francisco, California 94102

Stanford University
Department of Mathematics
Stanford, California 94305

Library
Courant Institute of
Mathematical Sciences
New York University
New York, New York 10012

Science Library
Brown 120
New York University
New York, New York 10012

Director, Naval Research
Laboratory
Attn: Library, Code 2029 (ONRL)
Washington, D.C. 20390

Technical Library
Naval Ordnance Station
Indian Head, Maryland 20640

Naval Ship Engineering Center
Philadelphia
Division Technical Library
Philadelphia, Pennsylvania 19112

Bureau of Naval Personnel
Navy Department
Technical Library
Washington, D.C. 20370

Naval Ordnance Station
Louisville, Kentucky 40214

Library
Naval Electronics Laboratory
Center
San Diego, California 92132

Naval Applied Science
Laboratory
Technical Library, Code 222
Flushing and Washington Avenues
Brooklyn, New York 11251

Naval Undersea Research and
Development Center, San Clemente
Island
3703 East Foothill Boulevard
Pasadena, California 91107
Technical Library

University of Chicago
Department of Statistics
Chicago, Illinois 60637
Attn: Prof. W. Kruskal

Florida State University
Department of Statistics
Tallahassee, Florida 32306
Attn: Prof. I. K. Savage

Princeton University
Department of Statistics
Princeton, New Jersey 08540
Attn: Prof. J. W. Tukey

Stanford University
Department of Statistics
Stanford, California 94305
Attn: Prof. T. W. Anderson

University of California
Department of Statistics
Berkeley, California 94720
Attn: Prof. P. J. Bickel

Cornell University
Department of Mathematics
White Hall
Ithaca, New York 14850
Attn: Prof. J. Kiefer

Purdue University
Department of Statistics
Lafayette, Indiana 47073
Attn: Prof. H. Rubin

University of Connecticut
Department of Statistics
Storrs, Connecticut 06268
Attn: Prof. H. O. Portier

Stanford University
Department of Mathematics
Stanford, California 94305
Attn: Prof. S. Karlin

Stanford University
Department of Statistics
Stanford, California 94305
Attn: Prof. H. Chernoff

Applied Mathematics Laboratory
Naval Ships Research
Development Center
Washington, D.C. 20007
Attn: Mr. Gene H. Gleissner

Systems Analysis Division
Room BE760, Pentagon
Washington, D.C. 20350
Attn: Mr. A. S. Rhodes, Cp-964

Southern Methodist University
Department of Statistics
Dallas, Texas 75222
Attn: Prof. D. B. Owen

University of Georgia
Department of Statistics
Athens, Georgia 30601
Attn: Prof. R. E. Bargmann

Rice University
Department of Mathematical
Sciences
Houston, Texas 77001
Attn: Prof. R. M. Thrall

Israel Institute of Technology
Technion
Haifa, ISRAEL
Attn: Prof. P. Naor

Program in Logistics
The George Washington University
707 22nd Street, N.W.
Washington, D.C. 20037
Attn: Dr. W. H. Marlow



JUN 22 1970

DATE DUE

JUL 23 1970

CAYLOR

PA NTED IN U S A

IMM-
382

c.1

Hirsch

Asymptotic performance of a
system subject to cannibalization.

IMM-
382

c.1

Hirsch

AUTHOR

Asymptotic performance of a
TITLE system subject to
cannibalization.

DATE DUE

BORROWER'S NAME

DEC 13 1964

Naselli

66

N.Y.U. Courant Institute of
Mathematical Sciences

251 Mercer St.

New York, N. Y. 10012

